



This page lists the contents included in the box. Please take time to identify the hardware as well as the individual components of the product. As you unpack and prepare for assembly, place the contents on a carpeted or padded area to protect them from damage. Please follow the assembly instructions closely. Improper assembly can result in personal or property damage.


IMPORTANT SAFETY INSTRUCTIONS:
If you are unsure about your ceiling type or what mounting method you should use, consult a qualified professional or your local hardware store.

We recommend installation of this lamp be performed by a licensed electrician.



hardware & components

800.606.6387



1 - lamp assembly



1 - mounting plate



2 - canopy bolts



2 - wire nuts



2 - mounting bolts




1 - 23 watt max CFL dimmable bulb (NOT INCLUDED)
 OR
 1 - 100 watt max type A standard bulb (NOT INCLUDED)


tools required



electrical tape




flat head screwdriver



phillips head screwdriver

cleaning & care

Dust surfaces with a dry soft cloth. Do not use cleaners or polishes on the lamp.



- 1) Shut off the main electrical supply from the main fuse box/circuit breaker.
 - 2) Carefully unpack all fixture parts and hardware. Lay items out on a clear workspace.
 - 3) Place the **mounting plate** over the center of the ceiling junction box.
 - 4) Align holes in **mounting plate** with holes in junction box and attach with 2 **mounting bolts**, using a **phillips head screwdriver**.
 - 5) Determine the length of chain required to hang the fixture at the desired height. With chain at the desired length (excess chain will lie next to the shade), attach the **quick link** to the chain and lamp shade and secure with the small nut.
 - 6) Gently pull wiring down from ceiling junction box and allow it to hang.
 - 7) Carefully inspect the lamp fixture's wires:
 - *Neutral fixture wire* = white
 - *Hot fixture wire* = black
 - *Ground wire* = green
 - 8) Attach the *ground wire* of the lamp assembly to the *ground wire* from the junction box and securely wrap around ground screw of the mounting plate. Tighten the ground screw with a **flat head screwdriver**.
 - 9) Attach the *neutral fixture wire* from the lamp to the *neutral junction box wire* (usually white). Fasten each together with a **wire nut** and wrap the connection with **electrical tape**.
 - 10) Attach the *hot fixture wire* from the lamp to the *hot junction box wire* (usually black). Fasten each together with a **wire nut** and wrap the connection with **electrical tape**.
- DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
- 11) Gently tuck wire connections neatly into the ceiling junction box.
 - 12) Fit **canopy** over **mounting plate** until it is flush to the ceiling. Align holes in canopy with holes in mounting plate and secure with 2 **canopy bolts**.
 - 13) Unfasten *rings* from bottom of shade to allow access to the socket. Insert 1- **bulb (not included)** into socket. DO NOT EXCEED SPECIFIED WATTAGE. Re-fasten rings to the shade to secure the assembly.
 - 14) Restore power to junction box and test fixture. Installation is now complete.