

Thank you for purchasing the **Tupelo Nightstand and Low Dresser**. This page lists all the contents included in the box. Please take the time to identify the hardware as well as the individual components to this product. As you unpack and prepare for assembly, place the contents on a carpeted or padded area to protect them from damage.

wall mounting hardware (low dresser only)

- 2 - wall straps
- 4 - wall brackets
- 2 - plastic anchors
- 4 - screws

tools required

- flat head screwdriver
- phillips head screwdriver

(We recommend the use of hand tools instead of power tools)

components

- 1 - nightstand assembly (pulls are pre-attached to inside of drawers)
- 1 - low dresser assembly (pulls are pre-attached to inside of drawers) **OR**

nightstand

low dresser

1 Pull on *red ribbon* to open *drawer assembly* of **nightstand and low dresser** (sold separately). Discard ribbon. Using a **phillips head screwdriver**, detach *bolts* from pre-attached *pull*. Set hardware aside. Repeat steps for each drawer.

nightstand

low dresser

2 Attach *pull* to front of *drawer assembly* with 2 *bolts*. Repeat steps for each drawer. Assembly is now complete.

warning (low dresser only)

The maximum weight this unit can support is 135lbs. Recommended that the maximum width of the TV is 20".

cleaning & care

Clean surfaces with a dry or damp soft cloth. Do not use abrasive cleaners. Do not use furniture wax or polish as the unit is finished with a protective clear lacquer.

safety mounting assembly for low dresser

For added safety and stability, it is recommended that the anti-tipping hardware be installed. Mount to wood studs whenever possible. For safe mounting, it is essential to use wall anchors appropriate to your wall type (i.e. plaster, drywall, concrete, etc.).

- A. Attach 1 **wall bracket** to upper left-hand corner of the assembled unit with 1 **screw** as shown. Secure, but do not over tighten, screws with a **phillips head screwdriver**.
- B. With the assistance of another adult, place the unit in desired location against the wall. Mark position on the wall, approximately 2" below the wall bracket mounted to the back of the unit. Move the unit out of the workspace.
- C. Drill 1 hole slightly smaller in diameter than the plastic anchor. Insert 1 **plastic anchor** into the hole until it is flush to the wall.
- D. Insert 1 **screw** through 1 **wall bracket** and into the plastic anchor.

At this point, repeat steps A-D for upper right-hand corner of assembled unit.

- E. Place the unit back into position against the wall. Lace one end of each **wall strap** through wall brackets, and into the other end of the strap.
- F. Pull the straps tightly until secure.

Wall mounting assembly is now complete.

NOTE: If you are unsure about your wall type or what mounting method you should use, consult a qualified professional or your local hardware store.

